

Sommario

SW1		Dip	DIP Settings				Function
1 2 3 4 5 6 7 8 OFF↔ON	1	OFF	Baud-rate 57600				PROG PORT transmission speed selection
		ON	Baud-rate 115200				
	2	OFF	Baud-rate 57600				USER PORT transmission speed selection
		ON	Baud-rate 115200				
	3	OFF	Can also be used by SERCOM and MODBUS device				PROG PORT function mode selection
		ON	Cannot be used by SERCOM and MODBUS device				
	4	OFF	ON	OFF	ON	Valid if in the CANOPEN device declaration is set the speed to 0)]	
	5	OFF	OFF	ON	ON		
6	Baud-rate 125KB/S	Baud-rate 250KB/S	Baud-rate 500KB/S	Baud-rate 1MB/S	External media device selection on the system functions		
7	OFF	MMC/SD					
8	ON	USB				Select the USER PORT as PROG PORT ¹⁾	
	Reserved. Leave OFF						
8	OFF	PROG PORT normal					
	ON	PROG PORT on the USER PORT connector					

¹⁾ It's possible to use the connector of the USER PORT as PROG PORT with RS232 electric standard. The mini-USB PROG PORT connector is unplugged (USER PORT electric standard setting). **For this function is necessary to set at OFF the dip 6 of the SW2.**

Documento generato automaticamente da **Qem Wiki** - <https://wiki.qem.it/>

Il contenuto wiki è costantemente aggiornato dal team di sviluppo, è quindi possibile che la versione online contenga informazioni più recenti di questo documento.