

## 目录

<b>AC10CtrlArr</b> .....	3
<b>IMPLEMENTATION</b> .....	3
Type .....	3



# AC10CtrlArr

**A** = Array

**C** = Calculate functions

The ControlArray function scans the values of an array, depending on the type of analysis required. The analysis type is passed as an argument; possible values are shown below in the Type paragraph.

## IMPLEMENTATION

### AC10CtrlArr (array, tipo, result, done)

Parameters:

IN/OUT	VARIABLE TYPE	EXAMPLE NAME	DIM	
IN	ARRSYS	array	L/S	Arrays for which you want to make a control
IN	GLOBAL	tipo	B	Specifies the analysis type (see "Type" section)
OUT	GLOBAL	result	F	Flag that indicates the result of the analysis.
OUT	GLOBAL	done	F	Flag that indicates that the operation completed

## Type

tipo = 1 the function sets the result to 1 if at least one of the values in the array is non-zero

tipo = 2 the function sets the result to 1 if all the values in the array are not zero

tipo = 3 the function sets the result to 1 if the majority of the values of the array is non-zero

## Example

Check the array, when the "gfConfronta" flag is set to 1, to see if all the values in the array are to 0.

```
IF gfConfronta
    gfConfronta = 0
    tipo = 1
    AC10CtrlArr (array, tipo, result, done)
    IF NOT result
        gfTuttiZero = 1
    ENDIF
ENDIF
```

## Note

- The function executes a WAIT a time every 180 milliseconds

Documento generato automaticamente da **Qem Wiki** - <https://wiki.qem.it/>

Il contenuto wiki è costantemente aggiornato dal team di sviluppo, è quindi possibile che la versione online contenga informazioni più recenti di questo documento.