

Sommario

VI10GetErrorCode	3
IMPLEMENTATION	3
Error code	3

VI10GetErrorCode

V = Vector

I = Image

Function that is used to manage the Vector Image function (object that resides on some Qpaint versions).

The VI10GetErrorCode function is used in order to know any kind of error occurred during drawing to Vector Image. At the end of the drawing procedure, after calling the “VI10WaitBufferReadyUsingWAIT” function or the “VI10WaitBufferReadyUsingEND” function to wait the end of the drawing, if you raise an error, through this function is used to determine the cause.

IMPLEMENTATION

VI10GetErrorCode (awBuffer,Error)

Parameters:

IN/OUT	VARIABLE TYPE	EXAMPLE NAME	DIM	
IN	ARRSYS / ARRGBL	awBuffer	W	Array that serves as a buffer for instructions/data
OUT	GLOBAL	Error	W	Variable containing the type of error

Error code

- No error
- Protocol error
- Non-compliant data
- Arc-Center calculation not possible

Example

TASK_00

```

MAIN:
VI10DrawBuffer(awBuffer )           ;Draws the contents of the Buffer
VI10WaitBufferReadyUsingEND( awBuffer )           ;Awaits the conclusion of the drawing
VI10GetErrorCode( awBuffer, Error )           ;Check if there are errors
IF (gwError GE 1) AND (gwError LE 3)
    JUMP ERROR
ENDIF

```

Note

Documento generato automaticamente da **Qem Wiki** - <https://wiki.qem.it/>
 Il contenuto wiki è costantemente aggiornato dal team di sviluppo, è quindi possibile che la versione online contenga informazioni più recenti di questo documento.