

Table of Contents

VR10BinToSBy	3
IMPLEMENTATION	3
Errcode	3

VR10BinToSBy

V = *Variables*

R = *Reading functions*

BINARIO → SIGNED BYTE

The VR10BinToSBy function converts a binary variable type in a Signed Byte type (byte with sign).

IMPLEMENTATION

VR10BinToSBy (array, index, return, errcode)

Parameters:

IN/OUT	VARIABLE TYPE	EXAMPLE NAME	DIM	
IN	ARRGBL	array	B	Array containing the data to be converted (must be declared at least "index" elements)
IN	GLOBAL	index	L	Index of the array element at the beginning the data
OUT	GLOBAL	return	B	Data value converted
OUT	GLOBAL	errcode	F	Variable that indicates a possible error on the function

Errcode

After calling the function, 'errcode' can take certain values, the meaning of these values is summarized below:

0: No error

Example

Transforms the value -5 (binary) in a signed byte value

```
index = 1
array[I] = -5
VR10BinToSBy (array, index, return, errcode)
;On the return data you will find :
; return = -5
```

Note

Documento generato automaticamente da **Qem Wiki** - <https://wiki.qem.it/>

Il contenuto wiki è costantemente aggiornato dal team di sviluppo, è quindi possibile che la versione online contenga informazioni più recenti di questo documento.