

Table of Contents

VR10BinToUWr 3

IMPLEMENTATION 3

 Errcode 3

VR10BinToUWr

V = Variables

R = Reading functions

BINARY → UNSIGNED WORD

The VR10BinToUWr function Converts a binary variable type in an Unsigned Word type (word without sign).

IMPLEMENTATION

VR10BinToUWr (array, index, return, errcode)

Parameters:

| IN/OUT | VARIABLE TYPE | EXAMPLE NAME | DIM | |
|--------|---------------|--------------|-----|--|
| IN | ARRGBL | array | B | Array containing the data to be converted (must be declared with at least "index + 1" items) |
| IN | GLOBAL | index | L | Index of the array element at the beginning of the data |
| OUT | GLOBAL | return | L | Data value converted |
| OUT | GLOBAL | errcode | F | Variable that indicates a possible error on the function |

Errcode

After calling the function, 'errcode' can take on certain values, the meaning of these values is summarized below:

0: No error

Example

Transforms the value 55346 (binary) in an unsigned word value

```
index = 1
array[1] = -40
array[2] = 50
VR10BinToUWr (array, index, return, errcode)
;On the return data you will find :
; return = 55346
```

Note

Documento generato automaticamente da **Qem Wiki** - <https://wiki.qem.it/>

Il contenuto wiki è costantemente aggiornato dal team di sviluppo, è quindi possibile che la versione online contenga informazioni più recenti di questo documento.